Installation: Convert from Http to Https (x86 systems)

Convert the existing Web-Console access from HTTP to SSL (HTTPS)

This Document is for x86 based systems

Organizations who want to start using https as the primary mode of connectivity for eScan WMC, should follow these steps:

1. Stop eScan-Apache Service using Service Control Window

2. Modify httpd.conf file located at path "C:\program files\common files\microworld\apache2\conf\httpd.conf"

Note: Take backup of file before Modifying

Locate the below mentioned lines in the conf and remove the preceding # #LoadModule ssl_module modules/mod_ssl.so

3. Modify "C:\program files\common files\microworld\apache2\conf\apache_escan_vhost.conf" Note: Take backup of file before Modifying

Locate the below mentioned lines in the conf and remove the preceding # #SSLPassPhraseDialog builtin #SSLSessionCache none #SSLMutex default #SSLRandomSeed startup builtin #SSLRandomSeed connect builtin #SSLEngine on #SSLCipherSuite ALL:!ADH:!EXPORT56:RC4+RSA:+HIGH:+MEDIUM:+LOW:+SSLv2:+EXP:+eNULL #SSLCertificateFile bin/ssl/webconsole.cer #SSLCertificateFile bin/ssl/webconsole.key #SSLCACertificateFile bin/ssl/webconsole.key #SSLCACertificateFile bin/ssl/ca.cer #SSLOptions +StdEnvVars

4. Launch Command prompt with Administrator priviliage and go to directory "C:\program files\common files\microworld\apache2\bin\SSL" and check if file webconsole.cer, webconsole.key, ca.cer is created or not during installation

5. If any of the above file is missing you need to regenerate SSL certificate Execute/run the file ssl_cert.exe to generate self-signed certificates necessary for SSL from directory "C:\program files\common files\microworld\apache2\bin"

Note: If ssl_cert.exe file is not present, kindly download from below link http://www.microworldsystems.com/download/tools/ssl_cert.exe

6. Pause eScan Protection and go to directory "C:\program files\eScan")

Page 1 / 2

(c) 2024 eScan <sachinr@mwti.net> | 2024-04-20 12:53

Installation: Convert from Http to Https (x86 systems)

Open eserv.ini and change the value of UseHTTPs from "0" to "1" in Config Section.

7. Restart the system

8. Browse to https://localhost:10443 or https://ipaddress:10443 and add the Self-Signed certificate to the ssl-store of the browser.
Unique solution ID: #1151
Author: eScanQA
Last update: 2015-10-19 11:28